

BOGE SO-3 series

Oil-free with maximum efficiency

GRANZOW

svensk tryckluftspartner



TECHNICAL DATA

BOGE type	Maximal pressure	Effective free air delivery* (50 Hz)		Rated output main drive	Fan motor	Dimensions soundproofed	Weight soundproofed
		min	max				
	bar	m³/min	m³/min	kW	kW	B x T x H (mm)	kg
SO 110-3	7.5	—	19.80	110	0,75	3086 x 1820 x 2010	3800
	8	—	17.60	110	0,75	3086 x 1820 x 2010	3800
	10	—	15.50	110	0,75	3086 x 1820 x 2010	3800
SO 132-3	7.5	—	24.60	132	0,75	3086 x 1820 x 2010	3950
	8	—	21.30	132	0,75	3086 x 1820 x 2010	3950
	10	—	19,70	132	0,75	3086 x 1820 x 2010	3950
SO 160-3	7.5	—	29.10	160	0,75	3086 x 1820 x 2010	4030
	8	—	26.30	160	0,75	3086 x 1820 x 2010	4030
	10	—	24.50	160	0,75	3086 x 1820 x 2010	4030
SO 110-3 F	7.5	9.33	20.34	110	0,75	3086 x 1820 x 2010	4120
	8	9.23	19.61	110	0,75	3086 x 1820 x 2010	4120
	10	8.06	17.00	110	0,75	3086 x 1820 x 2010	4120
SO 132-3 F	7.5	10.72	23.84	132	0,75	3086 x 1820 x 2010	4270
	8	9.23	21.71	132	0,75	3086 x 1820 x 2010	4270
	10	8.06	19.27	132	0,75	3086 x 1820 x 2010	4270
SO 160-3 F	7.5	12.83	29.02	160	0,75	3086 x 1820 x 2010	4350
	8	11.50	26.40	160	0,75	3086 x 1820 x 2010	4350
	10	10.58	24.47	160	0,75	3086 x 1820 x 2010	4350

* Delivery quantity measured on ISO 1217: 2009 annex C